

The coil chart shows applicable voltages for various frequencies. Specify voltages and frequencies as listed below when ordering. Consult factory for voltages and frequencies not listed.

SERIES 70 COIL CHART

A.C. VOLTAGES		D.C. VOLTAGES	NON-MOLDED COIL NO.	MOLDED COIL NO.
60 HZ.	50 HZ.			
12	11	2.5	7C-101-A24	7C-1-K24
16	14	3.3	7C-102-A24	7C-2-K24
24	21	5	7C-103-A24	7C-3-K24
28	25	6	7C-104-A24	7C-4-K24
			7C-105-A24	7C-5-K24
41	37	8	7C-106-A24	7C-6-K24
48	43	10	7C-107-A24	7C-7-K24
55	49	12	7C-108-A24	7C-8-K24
97	87	20	7C-109-A24	7C-9-K24
110	98	24	7C-110-A24	7C-10-K24
120	110	26	7C-111-A24	7C-11-K24
140	124	28	7C-112-A24	7C-12-K24
150	135	32	7C-113-A24	7C-13-K24
240	220	50	7C-114-A24	7C-14-K24
204	182	46	7C-115-A24	7C-15-K24
395	355	82	7C-116-A24	7C-16-K24
480	430	100	7C-117-A24	7C-17-K24
540	485	120	7C-118-A24	7C-18-K24
575	515	125	7C-119-A24	7C-19-K24
1050	940	220	7C-120-A24	7C-20-K24
159	143	36	7C-121-A24	7C-21-K24
1150	1035	250	7C-122-A24	7C-22-K24
315	287	67	7C-123-A24	7C-23-K24
338	307	72	7C-124-A24	7C-24-K24
960	860	198	7C-125-A24	7C-25-K24

EXPORT COILS

13	12	2.7	7CE-102-A24	7CE-2-K24
26	24	5.3	7CE-104-A24	7CE-4-K24
53	48	11.5	7CE-107-A24	7CE-7-K24
100	90	21	7CE-109-A24	7CE-9-K24
112	100	25	7CE-110-A24	7CE-10-K24
140	127	30	7CE-113-A24	7CE-13-K24
255	230	53	7CE-114-A24	7CE-14-K24
265	240	60	7CE-115-A24	7CE-15-K24
420	380	92	7CE-116-A24	7CE-16-K24
490	440	102	7CE-117-A24	7CE-17-K24
225	204	48	7CE-120-A24	7CE-20-K24

DIODE RECTIFIED COILS

24	24		7CD-108-A24	
	115/400 Hz		7CD-114-A24	
120	110 & 120		7CD-115-A24	
240	220 & 240		7CD-118-A24	

Valve Temperature Range: STANDARD VALVES – 0°F (-18°C) to 104°F (40°C) ambient; 0°F (-18°C) to 150°F (65°C) media. OPTIONAL VALVES – can tolerate much higher or much lower ambient and media temperatures. Consult factory for specifics.