

SOLENOID VALVES . . .

AVAILABLE OPTIONS

HOUSING & COIL OPTIONS	OPTION CODE	SERIES					COMMENTS
		15	20	30	50	70	
Strain Relief Connector	Q		✓	✓	✓	✓	Standard no-molded – Others Consult Factory
Single Automotive	AS		✓	✓		✓	Requires potting – Consult Factory
Double Automotive	AD		✓			✓	Requires potting – Consult Factory
“AN” Connector (2 Wire)	S		✓	✓	✓	✓	Recommended potting/other option – Consult Factory
J.I.C. Housing	J		✓				
Yoke – For Leads	Y		✓	✓	✓		Non-molded coil or Molded
Mounting Bracket	B	✓	✓	✓	✓	✓	Series 20 E.P. Special - Consult Factory
Splice Box	N		✓	✓	✓	✓	
Metered Exhaust Port	U		✓	✓			
Metered Exhaust Adapter	—		✓	✓			
Built-in Muffler	V	✓	✓	✓	✓	✓	(For use with valve adapter)
Potted Coil in Housing	P		✓	✓	✓	✓	
Spade Terminal Coil – Molded	KM		✓	✓	✓	n/a	
Universal Mounting Bracket	20-2416	✓	✓	✓	✓	n/a	
Universal Bracket Top Mount	B96	✓	✓	✓	✓	✓	
3RD Wire Ground	CC		✓	✓	✓	✓	
Weather Proof Seal	W		✓	✓	n/a	n/a	
Aluminum Shading Rings	A	✓	✓	✓	✓	✓	
Silver Shading Rings	S	✓	✓	✓	✓	✓	Consult Factory for price fluctuations
Series E 50 All Stainless Steel Explosion Proof Option					✓		Consult Factory for details
Series EL 50 Explosion Proof Low Watt Option					✓		Consult Factory for details
Series EL 50 Stainless Steel Explosion Proof Low Watt Option					✓		Consult Factory for details
Series ELL-50 Extra Low Watt Option					✓		Consult Factory for details
Time Option Net Adder Any Quantity			✓				S-20 European Coil. Consult Factory.

VALVE BODY & PORT OPTIONS

Consult factory for minimum quantities

	OPTION CODE	SERIES					COMMENTS
		15	20	30	50	70	
Metering to 1/8" Orifice	T		✓	✓	✓	✓**	
Metering to 1/4" Orifice	F		✓			✓	
Metered Bypass	W		✓			✓	
Manual Override	Y		✓*			✓	
Bottom Orifice Port	R		✓	✓	✓	✓	
Bottom Cavity Port	O		✓	✓	✓	✓	
Port 90° Left	M		✓	✓		✓	
Manifold Mount	E	†	✓	✓	✓	✓	
Flange mount	H		✓			✓	
Port 90° Right	L		✓	✓			
Gang Feeding (3 Ported Body)	G		✓	✓			
10/32 Ports					✓		

* Manual override not available in high pressure - Series 20 valves.

** Possible only with 3/32 & 1/8 Orifice. (Restricts flow with 1/8 orifice.)

† Square aluminum body-top mounting. (Consult factory.)